



PCR2000/2.0

**PCR2000 c/w 3 Core 0.75mm<sup>2</sup> 2m PVC Lead**

**Technical characteristics**

**Architecture**

|                 |   |
|-----------------|---|
| Number of poles | 3 |
|-----------------|---|

**Voltage**

|                        |       |
|------------------------|-------|
| Max. operating voltage | 240 V |
|------------------------|-------|

**Electric current**

|               |     |
|---------------|-----|
| Rated current | 6 A |
|---------------|-----|

**Cable**

|                |      |
|----------------|------|
| Cable diameter | 7 mm |
|----------------|------|

|                                          |       |
|------------------------------------------|-------|
| Cable permanent temperature resistant to | 90 °C |
|------------------------------------------|-------|

**Dimensions**

|        |          |
|--------|----------|
| Length | 2,000 mm |
|--------|----------|

**Connection**

|                         |                             |
|-------------------------|-----------------------------|
| Conductor cross-section | 0.75 - 0.75 mm <sup>2</sup> |
|-------------------------|-----------------------------|

**Equipment**

|                   |     |
|-------------------|-----|
| Mechanical coding | Yes |
|-------------------|-----|

|                   |      |
|-------------------|------|
| Type cable side 1 | Plug |
|-------------------|------|

|                   |                    |
|-------------------|--------------------|
| Type cable side 2 | Free conductor end |
|-------------------|--------------------|

**Use conditions**

|                                                             |   |
|-------------------------------------------------------------|---|
| Degree of pollution according to IEC 60664 /<br>IEC 60947-2 | 2 |
|-------------------------------------------------------------|---|

**Materials**

|        |       |
|--------|-------|
| Colour | White |
|--------|-------|