



5MP Light & Siren Active Deterrent Camera

CODE: CTX5C-IP-AD-TUR-S3FW



Fixed
Lens



5MP
Resolution



30m Dual-Light
Range



People and
Vehicle Detection



Active
Deterrent



Camera

Image Sensor	1/2.7" CMOS
Image Resolution	5MP (2960 x 1688)
ROM	256MB
RAM	1GB
Scanning System	Progressive
Electronic Shutter Speed	Auto / Manual; 1/3s to 1/100,000s
Minimum Illumination	0.003 lux @ F1.0 (Colour, 30 IRE); 0.0003 lux @ F1.0 (Black / White, 30 IRE); 0 lux (Illuminator On)
S/N Ratio	>56dB
Illumination Distance	30m (98.43 ft.) (IR & Warm Light)
Illuminator On / Off Control	Auto / Manual
Illuminator Number	1 (IR LED); 1 (Warm Light)
Pan / Tilt / Rotation Range	Pan: 0°–360°; Tilt: 0°–78°; Rotation: 0°–360°



5MP Light & Siren Active Deterrent Camera

CODE: CTX5C-IP-AD-TUR-S3FW



Lens Information

Lens Type	Fixed Focal			
Lens Mount	M12			
Focal Length	2.8mm			
Maximum Aperture	F1.0			
Field of View	Horizontal: 97°; Vertical: 70°; Diagonal: 128°			
Iris Control	Fixed			
Close Focus Distance	1.5m (4.92 ft.)			
DORI Distance	Detect	Observe	Recognise	Identify
	66m (216.54 ft.)	26.4m (86.61 ft.)	13.2m (43.31 ft.)	6.6m (21.65 ft.)

Intelligent Functions

IVS (Perimeter Protection)	Tripwire & Intrusion (Classification and Detection of People & Vehicles)
SVD 4.0 (People & Vehicle Detection +)	Supported
AI Target Location	Uses Deep Learning Algorithms to Accurately Match Targets & Search Through Live and Recorded Footage to Locate Targets
AI SSA	Supported
Intelligent Search	(With Smart NVR) Perform Refined Intelligent Search, Event Extraction and Merging for Event Videos

Video

Video Compression	H.265 / H.264 / H.264H / H.264B / MJPEG (Only Supported by Sub-Stream)
Smart Codec	Smart H.265+ / Smart H.264+
AI Coding	AI H.265 / AI H.264
Video Frame Rate (These values are the maximum frame rates of each stream. For multiple streams, the values will be subjected to the total encoding capacity.)	Main Stream: 2880 x 1620 / 2960 x 1668 @ (1-20 fps) / 2688 x 1520 @ (1-30 fps)
	Sub Stream 1: 704 x 576 @ (1-25 fps) / 704 x 480 @ (1-30 fps)
	Sub Stream 2: 1920 x 1080 @ (1-25/30 fps)



5MP Light & Siren Active Deterrent Camera

CODE: CTX5C-IP-AD-TUR-S3FW

Video (continued.)

Stream Capability	3 Streams
Resolution	5MP (2880 x 1620 / 2960 x 1668); 4MP (2688 x 1520 / 2560 x 1440); 3MP (2304 x 1296 / 2048 x 1536); 1080P / 2MP (1920 x 1080); 1.3MP (1280 x 960); 720P (1280 x 720); D1 (704 x 576 / 704 x 480); CIF (352 x 288 / 352 x 240);
Bit Rate Control	CBR / VBR
Video Bit Rate	H.264: 3 kbps to 16384 kbps; H.265: 3 kbps to 16384 kbps
Day / Night	Auto (ICR), Colour or Black / White
BLC	Supported
HLC	Supported
WDR	120 dB
Scene Self Adaptation (SSA)	Supported
White Balance	Auto, Natural, Street Lamp, Outdoor, Manual, Regional, Custom
Gain Control	Auto
Noise Reduction	3D NR
Motion Detection	On / Off (4 Rectangular Areas)
Region of Interest (RoI)	Supported (4 Areas)
Defog	Supported
Image Rotation	0° / 90° / 180° / 270° (Supports 90° / 270° with 4MP Resolution (2688 x 1520) and Lower)
Mirror	Supported
Privacy Masking	Supported (4 Areas)



5MP Light & Siren Active Deterrent Camera

CODE: CTX5C-IP-AD-TUR-S3FW



Audio

Built-In Microphone & Speaker	Yes
Audio Compression	G.711a; G.711Mu; PCM; G.726; G.723

Alarm

Alarm Event	Alarm in Case Of: - No SD Card - Full SD Card - SD Card Error - Network Disconnection - IP Conflict - Illegal Access - Motion Detection - Video Tampering - Intrusion - Tripwire - Scene Change - Audio Detection - Voltage Detection - Defocus Detection - People & Vehicle Detection - Safety Exception
-------------	---



Network

Network Port	RJ45 (10 / 100 Base-T)
SDK & API	Supported
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; SNMP; P2P
Cyber Security	Video Encryption; Firmware Encryption; Configuration Encryption; Digest; WSSE; Account Lockout; Security Logs; IP / Mac Filtering; Generation and Importing of X.509 Certification; Syslog; HTTPS; 802.1x; Trusted Boot; Trusted Execution; Trusted Upgrade
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone
User / Host	20 (Total Bandwidth: 64MB)
Storage	FTP; SFTP; Micro SD Card (Max. 256 G); NAS
Browser	IE8 / 9 / 11; Chrome; Firefox
Management Software	λ Cortex VMS
Mobile Client	iOS & Android



5MP Light & Siren Active Deterrent Camera

CODE: CTX5C-IP-AD-TUR-S3FW

Certification

Certifications

- CE-LVD: EN62368-1
- CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU
- FCC: 47 CFR FCC Part 15, Subpart B



Ports

Audio Input	1 Channel (RCA Port)
Audio Output	1 Channel (RCA Port)
Alarm Input	1 Channel In (Wet Contact, 5 mA 3V-5 VDC)
Alarm Output	1 Channel Out (Wet Contact, 300 mA 12 VDC)

Parameters & Dimensions

Power Supply	12VDC / PoE (802.3af)
Power Consumption	Standard: 3.7W (12 VDC); 4.8W (PoE) H.265 + Main Stream + IR / Warm Light Intensity: 8.3W (12 VDC); 8.8W (PoE)
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Working Temperature	-40°C to +60°C (-40°F to +140°F)
Working Humidity	Less than 95% (RH)
Protection	IP67
Casing	Metal
Product Dimensions	110.9mm x Φ122mm (4.8" x Φ4.37")
Net Weight	750g (1.65lb)
Gross Weight	920g (2.03lb)