

		Key features
		High quality imaging with 3K, 2960 × 1665 resolution 2.8 mm fixed focal lens Up to 40 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic Smart-Hybrid light, optimize your security with flexible lighting options
Model Number		T259W-HS
Analog HD Camera		
Camera	Image sensor	3K CMOS
	Video Resolution	2960 (H) × 1665 (V)
	Signal System	PAL/NTSC
	Frame Rate	TVI: 3K@20 fps, 4 MP@25 fps/30 fps, 1080p@25 fps/30 fps AHD: 5 MP@20 fps, 4 MP@25 fps/30 fps CVI: 4 MP@25 fps/30 fps CVBS: PAL/NTSC
	Lens	2.8mm
	Min.Illumination	0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR
	Angle of View	Horizontal FOV: 104.9°, vertical FOV: 67.3°, diagonal FOV: 129.8°
	Supplement Light type	White Light; IR
	Supplement Light Range	IR : Up to 40 m, white Light : Up to 20 m
	Day/Night Mode	Auto/Color
	Wide Dynamic Range	Digital WDR
	Image Enhancement	DWDR/BLC/HLC/Global
	White Balance	Auto/Manual
	AGC	Yes
	Built-in Microphone	Yes
	Video Output	BNC, switchable TVI/AHD/CVI/CVBS
General	Housing	Body: Metal Enclosure: Plastic
	Color	White
	Operating Power	12 VDC ± 25%
	Consumption	Max. 3.3 W
	Operating Temperature	-40 °F – 140 °F / -40 °C – 60 °C
	Indoor/Outdoor	Indoor/Outdoor

	Weatherproof Rating	IP67
	Dimension (L x W x H)	97.9 mm × Ø 110 mm (3.85" × Ø 4.33")
	Weight	Approx. 340 g (0.75 lb.)

