

**TITLE:**

Profinet Type A Type B

CODE:

SFX/PN-A-LSZH-D-GRN-1

DESCRIPTION:

1m (per metre) Profinet Type A, 4core
Green LSZH

SUPPLIED AS:

Per 1m Length

- **High-Speed Performance:** Profinet Type A cables are engineered to deliver exceptional data transfer speeds, ensuring seamless communication between industrial devices. With high-speed performance, your operations can run efficiently, minimizing delays and maximizing productivity.
- **Robust Reliability:** Built to withstand harsh industrial environments, Profinet Type A cables offer robust reliability. Their durable construction and resistance to interference and extreme temperatures ensure consistent performance, reducing downtime and maintenance costs.
- **Precise Signal Integrity:** These cables are designed to maintain precise signal integrity, enabling accurate and real-time data transmission. By minimizing signal loss and distortion. Profinet




IMAGE COMING SOON



IMAGE COMING SOON



IMAGE COMING SOON





Product Specification

25-YEAR WARRANTY



Cable Construction

CPR	Dca:S2,d2,a1
Conductor	Bare Copper
Conductor 3	solid
Conductor Diameter (mm)	0.645
Overall Diameter (mm)	6.5 ± 0.3 mm

Insulation

Insulation	HDPE
Insulation Colour	White,Blue, Yellow,Orange
Insulation Thickness (mm)	0.4
Insulation 2 Thickness (mm)	N/A
Outer Insulation	N/A
Outer Insulation Diameter (mm)	N/A
Outer Insulation Thickness (mm)	N/A

Outer/Jacket Specification

Outer Insulation	N/A
Outer Jacket	LSZH
Outer Jacket Colour	Green RAL 6018
Inner Jacket	YES
Inner Jacket Colour	natural
Inner Jacket Diameter (mm)	4.1
Inner Jacket Thickness (mm)	0.2
Jacket	LSZH
Overall Colour	Green RAL 6018
Overall Diameter (mm)	6.5 ± 0.3 mm
Jacket Colour	Green RAL 6018
Jacket Thickness (mm)	0.85 ± 0.15
Nylon Rip-Cord	N/A

Electrical Characteristics

Max Conductor DC resistance @ 20°C	≤ 57.5 Ω/km
Rated Temperature (°C)	-40 ~ +80 °C


enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



MORE INFORMATION:

EURO CLASS (ca: cable)	CLASSIFICATION CRITERIA		CPR GUIDE		
	FIRE RATING	SFX COMMENT	Securi-Flex®		
Reaction to Fire BS EN ISO 1716			SUBCLASSIFICATIONS FOR EUROCLASSES B _{ca} to D _{ca}		
A_{ca}	Does not contribute to the fire	Due to availability, it will be almost impossible for a cable to meet A _{ca} , so they should only be specified with extreme caution.	(S) SMOKE PRODUCTION	(D) FLAMING DROPLETS	(A) SMOKE ACIDITY
Reaction to Fire BS EN 50399			BS EN 50399/BS EN 61034-2	BS EN 50399	BS EN 60754-2
B1_{ca}	Minimum contribution to the fire	It's highly unlikely the commonly-used cables will be classified to Class B1 _{ca} .	s1a: s1 + transmittance ≥80% (BS EN 61034-2)	d0: No fall of droplets or flaming particles, times for 1200 seconds	a1: Very low acidity (conductivity <2.5 μS/mm & pH >4.3)
B2_{ca}	Combustible, low flame spread & heat release contribution to the fire	Similar to Class C _{ca} , although a lower acceptable heat release rate and burn measurement. In practice, this is likely to be the highest class cables will meet.	s1b: s1 + transmittance ≥60% <80% (BS EN 61034-2)	d1: Fall of droplets or flaming particles that persist for less than 10 seconds, timed for 1200 seconds	a2: low acidity (conductivity <10 μS/mm & pH >4.3)
C_{ca}	Combustible, moderate flame spread & heat release	This is a more rigorous test than Class D _{ca} , this is widely accepted across Europe as the 'go to' classification, but be aware, many cables do not meet Class C _{ca} though availability is improving.	s1: Low production of slow propagation of smoke		
D_{ca}	Combustible, moderate flame spread & heat release	This classification has relatively little use or acceptance within specifying/contracting organisations. This is because no large scale fire growth is measured.	s2: Intermediate production & propagation of smoke	d2: None of the above	d2: None of the above
Reaction to Fire BS EN 60332-1-2			Visit us online: www.securiflex.co.uk The Trusted Cable Brand		
E_{ca}	Combustible, limited fire spread of less than 425mm	A basic test for vertical flame propagation for a single insulated wire or cable using a 1 KW pre-mixed flame. Note: This test does not measure heat release, toxic fumes or smoke.	Classes A to E have to be tested by an independent authorised laboratory. Most cables will fall into classes B2 _{ca} to E _{ca} . For a cable to meet A _{ca} , B1 _{ca} , B2 _{ca} or C _{ca} , there also needs to be regular on-going factory audits.		
F_{ca}	Combustible, fire spread of more than 425mm	Cables classified to Class F _{ca} may have high levels of flammability due to the materials they are made of. This does not mean that the cable cannot be used, it is more likely to be used external.			

OUR OPERATING TEMPERATURE RANGE GUIDE



Securi-Flex®

enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23