



Product Codes

FLAT-50W-4000K

FLAT-100W-4000K

FLAT-200W-4000K



FLAT FLOOD LIGHT

50W - 100W - 200W

Available Power

5,000lm - 10,000lm - 20,000lm

Lumens Output



FLAT-50W-4000K
FLAT-100W-4000K
FLAT-200W-4000K

Flat Flood Light — Super Slim LED Floodlight

Specification

Range	50W, 100W, 200W
Colour temp	4000K
Output	100lm/W — 5,000lm / 10,000lm / 20,000lm
IP rating	IP66
Housing	Die-cast aluminium, driverless
Bracket	360° rotation
Flex	2m external-grade rubberised
Surge	4kV spike protection
Breather	Anti-fog waterproof
Cold start	Instant on, 100% output in cold conditions
Warranty	3 years

Dimensions

50W	W262.6 × H195.8 × D30.5mm
100W	W337.4 × H245.5 × D31.1mm
200W	W442.2 × H313.9 × D40.6mm

Product code & output

FLAT-50W	50W · 5,000lm
FLAT-100W	100W · 10,000lm
FLAT-200W	200W · 20,000lm

Selling points

- Slim profile — 30.5mm deep on the 50W
- IP66 aluminium body dissipates heat and extends fitting life
- Extensive 10W–200W range from one family

